

# CO 220 PE

## CONSTRUCTION PROPERTIES

### material data

		dimension
1° - Inner conductor: red copper	CU	∅ 2,20 mm
2° - Proofing in pigmentated Polyethylene with black carbon	PEC	
3° - Insulation: foam antiaging Polyethylene	PEE	∅ 9,90 mm
4° - Proofing in pigmentated Polyethylene with black carbon	PEC	
5° - Jelly filling	J 1	
6° - Tape: Aluminium/polyester/aluminium	AL/PET/AL	100 %
7° - Braid: tinned copper wires	CU - Sn	∅ 10,50 mm
8° - Jelly filling	J 2	
9° - Sheath: Polyethylene colours: BLACK	PE	∅ 12,00 mm



## ELECTRICAL SPECIFICATIONS

Screening Attenuation:	dB	>85
Braid coverage	%	65
DC Resistance: Inner Conductor	Ohm/Km	4,5
Outer Conductor	Ohm/Km	8,5
Nominal Impedance	Ohm	75 +/- 2
Capacitance approx	pF/m	52 +/- 2
Velocity ratio	%	85
Maximum voltage (spark test)	kV	8

Return Loss		SRL
Frequency		
20 - 470 MHz	dB	> 29
470 - 1500 MHz	dB	> 28
1500 - 2500 MHz	dB	> 23

Attenuation		dB/100 m	
Frequency			
5 MHz	dB	0,6	
50 MHz	dB	2,1	
200 MHz	dB	4,1	
300 MHz	dB	5,0	
470 MHz	dB	6,8	
860 MHz	dB	9,3	
1000 MHz	dB	10,0	
1750 MHz	dB	13,7	
2150 MHz	dB	15,0	
2500 MHz	dB	16,3	
3000 MHz	dB	18,5	

## MECHANICAL PROPERTIES

Minimum bending radius	mm	100
Total weight	Kg / Km	145
Copper weight	Kg / Km	58

TECHNICAL DATAS mod.TC15

latest issue date

01/09/2008

## CONFORMITY

EN50117-2-5  
EUROPEAN NORM RoHS

sign


